Optimal Randomized Parallel Algorithms for Computational Geometry

Pat Morin

Abstract

A summary of the results achieved in the paper "Optimal Randomized Parallel Algorithms for Computational Geometry," by Reif and Sen is given. These results include optimal randomized PRAM algorithms for the construction of Kirkpatrick's point location structure, and the construction of a data structure called a nested plane sweep tree. The plane sweep tree is used to solve a number of popular computational geometry problems optimally. All results hold with high probability.

1 Introduction

Parallel algorithms for computational geometry problems have received much attention from the algorithms community in recent years. Many of these algorithms make use of randomization to make the problems tractable.

In [?] Reif and Sen present a number of randomized algorithms for computational geometry problems which run in logarithmic time using a linear number of processors. Most of these algorithms are based on a data structure which the authors call a *nested plane sweep tree*. The goal of this work is to provide a simplified treatment of the results obtained in Reif and Sen's paper. All these algorithms run on the CREW PRAM.

The remainder of the paper is organized as follows: Section ?? reviews Kirkpatrick's point location data structure and presents a parallel algorithm for building this structure in logarithmic time. Section ?? reviews the well known segment tree data structure and its parallel counterpart the plane sweep tree. Section ?? defines the nested plane sweep tree and presents a parallel algorithm for its construction. Section ?? shows how the nested plane sweep tree can be used to solve a number of popular geometric problem in logarithmic time. Finally, Section ?? concludes and presents some open problems in this area.

2 Parallelizing Kirkpatrick's Algorithm

Recall Kirkpatrick's algorithm [?] for point location in a triangulated planar straight line graph. The algorithm proceeds in rounds. During each round, a maximal independent set of bounded degree vertices is chosen and deleted. The "holes" created by these deletions are then retriangulated. Kirkpatrick showed that the size of this set is a constant fraction of the total number of vertices in the graph. Thus, after $O(\log n)$ rounds, the graph is reduced to a constant number of vertices. Finding the independent set takes time linear in the current number of vertices, yielding linear time algorithm.

In order to create an $O(\log n)$ time parallel algorithm, we need to reduce the time needed to choose the independent set to $O(1)$. To achieve this we use a generalization of a technique known as *random mate*. The algorithm for choosing our independent set works as follows:

Algorithm Choose-Independent-Set:

1. Assign a sex (male/female) with equal probability to each vertex with degree $\leq d$. The males are the candidates for an independent set.

2. For each edge, if it connects two male vertices, then mark both vertices as dead.

3. The independent set consists of the set of all living male vertices.

Clearly this method produces an independent set of vertices and runs in constant time. The question which remains is to determine whether the size of the independent set is a constant fraction of the number of vertices in the graph. To see this we consider the following. It can be shown that there exists an independent set, S of degree $\leq d$ and of size αn, $0 < \alpha < 1$, for which the shortest path between any two vertices in S is of distance 3. With high probability, roughly half of the vertices of S are male. The probability of any particular male surviving is at least $\frac{1}{2^d}$ since it has at most d neighbours. Since d is a constant, this probability is a constant. Also, the probability of a given male in S surviving is independent of any other male in S surviving. Thus we can apply Chernoff bounds to show that the number of surviving males is $\tilde{O}(n)$

This yields an $\tilde{O}(\log n)$ algorithm for constructing Kirkpatrick's point location structure on a triangulated planar straight line graph using $O(n)$ processors. The number of processors can be reduced to $O(\frac{n}{\log n})$ using the well known technique of processor scheduling, thereby making the algorithm work-optimal.

This work also has applications to the construction of Voronoi diagrams. Using concurrent read capability, n queries can be executed on a planar subdivision of size n in $\tilde{O}(\log n)$ time using $O(n)$ processors. In [?], an algorithm is given for constructing the Voronoi diagram of n points in the plane in $O(\log^3)$ time using $O(n)$ processors. This algorithm consists of $O(\log n)$ rounds in which each round consists of performing point n point location queries. Thus using the scheme presented above, the running time of the Voronoi diagram construction algorithm can be improved to $\tilde{O}(\log^2 n)$.